



# CARECHLOR

## Heavy duty water based alkaline tank cleaner

- Effective dye removal
- Suitable on zinc and epoxy coatings.
- Approved by:  
> IMO

### DESCRIPTION

Carechlor is a high alkaline, chlorine based product for the removal of discoloration stains in cargo tanks caused by soot or red/ and or yellow dyed gasoline cargoes from epoxy and zinc based tank coatings.

### ADVANTAGE

- Suitable on epoxy and zinc tank coatings
- Fast acting
- Biodegradable
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds.
- Free from hydrocarbon solvents
- Effective and economical in use

### APPLICATIONS

#### *Tank Cleaning*

Carechlor is generally used for removing soot stain deposits from zinc and epoxy coated tanks. It is also very effective for bleaching of stains caused by the carriage of dyed gasoline cargoes.

### DIRECTIONS FOR USE

Carechlor is used in a 1-3% solution in fresh or seawater. Circulate at ambient temperatures for 2 – 4 hours. One solution usually is sufficient to clean 3-4 tanks. After this cleaning rinse thoroughly with a sufficient amount of fresh water.

### DOSAGE

Circulation                      1 - 3% solution

discover the difference



## PROPERTIES

Article number	14616 / 16616
pH (1 % solution)	> 11
Density	1,20 g/cm <sup>3</sup>
Flashpoint	None
Physical state	Liquid

## APPROVALS

- IMO approved in accordance with MEPC 590 Guidelines

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

## CARECHLOR

- Effective dye removal
- Suitable on zinc and epoxy coatings.
- Approved by:  
> IMO

discover the difference

MARINE CARE BV  
Mozartlaan 3  
3144 NA Maassluis  
The Netherlands  
T. +31 (0)10 2950342  
F. +31 (0)10 2950345  
E. [supply@marinecare.nl](mailto:supply@marinecare.nl)  
W. [www.marinecare.nl](http://www.marinecare.nl)