

# CARECLEAN DYE OUT

## Removing discoloration stains caused by soot or dyes

- Fast acting
- Highly concentrated

### DESCRIPTION

Careclean Dye Out is liquid a high alkaline and chlorine based product for the removal of discoloration stains caused by soot or fuel dyes from epoxy and zinc based tank coatings.

### ADVANTAGE

- Suitable on epoxy and zinc tank coatings
- Fast acting
- Highly concentrated
- Bleaching effect

### APPLICATIONS

#### *Tank Cleaning*

Careclean Dye Out is generally used for removing soot stain deposits from zinc and epoxy coated tanks. It is also very effective for bleaching of stains caused by the carriage of dyed gasoline cargoes.

### DIRECTIONS FOR USE

Careclean Dye Out is used in a 2 % solution in fresh water. Circulate at ambient temperatures for 1- 2 hours. After this cleaning rinse thoroughly with a sufficient amount of fresh water. For heavier and more stubborn stains wash with a 5 % solution or use pure as spray method.

### DOSAGE

|             |                  |
|-------------|------------------|
| Circulation | 2 - 5 % solution |
| Spraying    | undiluted        |

discover the difference



## PROPERTIES

|                   |                        |
|-------------------|------------------------|
| Article number    | 16614                  |
| pH (1 % solution) | 7,8                    |
| Density           | 1,23 g/cm <sup>3</sup> |
| Flashpoint        | None                   |
| Physical state    | Liquid                 |

## APPROVALS

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

## CARECLEAN DYE OUT

- Fast acting
- Highly concentrated

discover the difference

**MARINE CARE BV**  
Mozartlaan 3  
3144 NA Maassluis  
The Netherlands  
T. +31 (0)10 2950342  
F. +31 (0)10 2950345  
E. [supply@marinecare.nl](mailto:supply@marinecare.nl)  
W. [www.marinecare.nl](http://www.marinecare.nl)