

CARECLEAN CAUSTIC SODA

Heavy duty alkaline tank cleaner

- Removes fat and vegetable oil residues
- Biodegradable
- Approved by:
> IMO

DESCRIPTION

Careclean Caustic Soda is extremely efficient to remove vegetable oil and fat in cargo tanks in Tankers caused by carriage of vegetable oils.

ADVANTAGE

- Heavy duty tank cleaner
- Removes fat and vegetable oil residues
- Does not contain nonyl phenolic ethoxylates or other estrogenic compounds
- Biodegradable
- Free from hydrocarbon solvents
- Effective and economical in use
- Completely safe to use on epoxy coatings

DIRECTIONS FOR USE

Careclean Caustic Soda is mixed in a solution of 1-5% solution in fresh or seawater. Circulate the solution 2 – 6 hours. One solution usually is sufficient to clean 3-4 tanks. After this cleaning rinse thoroughly with a sufficient amount of fresh water.

DOSAGE

Circulation 1 - 5% solution

discover the difference



PROPERTIES

Physical state	Granular
Odour	None
Colour	White
Solubility in water	580 g/l v/ 20°C
pH value	14
Specific Gravity	2,13 kg/cm ³ v/ 20°C
Flashpoint	None

APPROVALS

- IMO approved in accordance with MEPC 590 Guidelines

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

CARECLEAN CAUSTIC SODA

- Removes fat and vegetable oil residues
- Biodegradeble
- Approved by:
> IMO

discover the difference

MARINE CARE BV
Mozartlaan 3
3144 NA Maassluis
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl