

CROSS REFERENCE LIST

TANKCLEANING PRODUCTS - CARGO - COATING - CLEANING - APPROVALS



	Mineral Oils / Greases - White / CPP	Mineral Oils / Greases - Black / DPP	Resins/Parafins	Greases / Waxes	Fatty acids / FAME's	Animal/Vegetable Oils & Fats	Soot Deposits	White Deposits	Stainless Steel Treatment	Inhibitor Killing/Removing	Smell Killing/ Air Freshing	Discoloration	Zinc Coat Conditioning	Hydrocarbon Free Cleaning	Stainless Steel	Zinc Coatings	Epoxy Coatings	Cleaning Method R = Recirculation DI = Direct Injection MS = Manual Spraying	IMO Approved - according MEPC 590	Typical Dilution	Typical Temperature Range
Careclean Air Fresh											✓				✓	✓	✓	R/MS	✓	0,1-1%	20-80°C
Careclean Alkaline	✓				✓	✓	✓								✓		✓	R/D/MS	✓	1-5%	20-60°C
Careclean Alkaline Extra	✓				✓	✓	✓								✓		✓	R/D/MS	✓	1-5%	60-80°C
Careclean Aquawash	✓				✓									✓	✓	✓	✓	R/D/MS	✓	1-5%	50-80°C
Careclean Buffer										✓			✓		✓	✓	✓	R/D/MS	✓	10%	45°C
Careclean Degreaser GP	✓			✓											✓	✓	✓	R/D/MS	✓	2-5%	50-80°C
Careclean Degreaser HD	✓	✓		✓											✓	✓	✓	R/D/MS	✓	2-6%	60-80°C
Caretank ECO	✓	✓	✓	✓	✓	✓	✓			✓			✓	✓	✓	✓	✓	R/D/MS	✓	0,2-1%	20-70°C
Carechlor										✓		✓				✓	✓	R/D/MS	✓	1-3%	20-50°C
Careclean Energy Wash	✓	✓		✓	✓	✓								✓	✓	✓	✓	R/D/MS	✓	1-3%	50-80°C
Careclean GP Enviro	✓			✓	✓	✓								✓	✓	✓	✓	R/D/MS	✓	1-5%	50-80°C
Careclean Inhibitor Killer										✓					✓	✓	✓	R/D/MS	✓	2-4%	60-80°C
Careclean Formula #3					✓	✓									✓	✓	✓	R/D/MS	✓	2-5%	50-80°C
Careclean Multiclean	✓			✓	✓	✓								✓	✓	✓	✓	R/D/MS	✓	2-5%	60-80°C
Careclean Neutral HCF	✓				✓	✓								✓	✓	✓	✓	R/D/MS	✓	2-3%	20-70°C
Careclean Passivation Liquid									✓						✓			R	✓	100%	Ambient
Careclean Pickling Liquid									✓						✓			R		100%	Ambient
Careclean SC	✓			✓	✓	✓	✓							✓	✓	✓	✓	R/D/MS	✓	0,5-2%	50-75°C
Careclean Rust					✓	✓		✓	✓						✓		✓	R/D/MS	✓	0,5-3%	50-80°C
Careclean Voyage	✓	✓	✓	✓											✓	✓	✓	R/D/MS	✓	2-6%	50-70°C

discover the difference