



**MARINE
CARE**

CARECLEAN DYE OUT

Removing discoloration stains caused by soot or dyes

- Fast acting
- Highly concentrated

DESCRIPTION

Careclean Dye Out is liquid a high alkaline and chlorine based product for the removal of discoloration stains caused by soot or fuel dyes from epoxy and zinc based tank coatings.

ADVANTAGE

- Suitable on epoxy and zinc tank coatings
- Fast acting
- Highly concentrated
- Bleaching effect

APPLICATIONS

Tank Cleaning

Careclean Dye Out is generally used for removing soot stain deposits from zinc and epoxy coated tanks. It is also very effective for bleaching of stains caused by the carriage of dyed gasoline cargoes.

DIRECTIONS FOR USE

Careclean Dye Out is used in a 1 - 3 % solution in fresh water. Circulate at ambient temperatures for 2 - 4 hours. For heavier and more stubborn stains wash with up to 5 %. One solution usually is sufficient for 3 - 4 tanks. After this cleaning rinse thoroughly with a sufficient amount of fresh water.

DOSAGE

Circulation	1 - 3 % solution
Spraying	5 - 10 % solution



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl

PROPERTIES

Article number	16614
pH (1 % solution)	7,8
Density	1,23 g/cm ³
Flashpoint	None
Physical state	Liquid

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.



MARINE CARE

**CARECLEAN
DYE OUT**

- Fast acting
- Highly concentrated



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl